(19) World Intellectual Property Organization

International Bureau



7

(43) International Publication Date 31 March 2005 (31.03.2005)

PCT

(10) International Publication Number WO 2005/028264 A1

(51) International Patent Classification⁷:

B60R 21/26

(21) International Application Number:

PCT/SE2004/001266

(22) International Filing Date:

3 September 2004 (03.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0322519.0

25 September 2003 (25.09.2003) GB

(71) Applicant (for all designated States except US): AUTO-LIV DEVELOPMENT AB [SE/SE]; S-447 80 Vårgårda (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HABERZETTL, Andreas [DE/DE]; Flutkanal 6, D-84405 Dorfen (DE). KLOSS, Markus [DE/DE]; Hollerner Str. 21, D-85386 Eching (DE).

(74) Agent: MEULLER, Erik; Autoliv Development AB, S-447 83 Vårgårda (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVEMENTS IN OR RELATING TO A GAS DEFLECTOR



(57) Abstract: A gas deflector (24) is disclosed for use with a cylindrical gas generator (20). The gas deflector (24) comprises a generally tubular housing to accommodate the cylindrical gas generator (20). The housing has two terminal portions (25, 26) of generally circular cross-section and has an intermediate region provided with an outwardly-extending formation (28). The outwardly-extending formation (28) defines, at either end thereof, an opening (31, 34) through which gas may flow in the direction substantially parallel to the axis of the housing.

28264 A1